

IC-A110 IC-A110EURO

Rugged
MIL-STD 810



Rugged and reliable for serious ground crew communications

Setting a new standard for ground based communications, the IC-A110 /EURO provide durability and reliability in demanding operational environments.

- **Capable of being installed in any vehicle**
IC-A110/EURO are adaptable to vehicles working on a 12 V, as well as a 24 V power source.
- **Front mounted loud speaker**
A loud speaker mounted in the front of the transceiver is free of any obstacles blocking audio reproduction. And 10 W, of powerful output power is available for the external speaker.
- **Dial selection**
With a simple rotation of the dial, frequently used memory channels, or desired frequency selection can be made.

- **Memory channel name capability**
Up to 7-character memory names can be assigned for each channel. Allows simple and quick channel recognition and selection.
- **Side tone function**
Operator's transmitted messages and calls are audio modulated and can be heard by standard airband headsets*, even in the most demanding operating airport conditions.
*Option OPC-871 is necessary when using standard type headset.
- **Convenient on hook scan functions**
Hanging the microphone on the mic. hanger activates the auto scan function. When released, the transceiver will return to the last used, or priority channel, depending on the selection.
- **Usable in extreme cold**
The adopted LCD guaranteed usable in temperatures from -30°C to $+70^{\circ}\text{C}$ (-22°F to $+158^{\circ}\text{F}$). Normal performance, as well as display indications, are guaranteed even in extremely cold areas.

ADDITIONAL FEATURES

- Additional to the predominantly used 25 kHz channel spacing, an extra version complying to new regulations is available for 8.33 kHz channel spacing
- Equipped EEPROM system provides maintenance free memory backup capability, without the use of a separate backup battery
- Various scan functions, such as VFO and priority scans are available
- Limited number of keys for simple manipulation, but providing advanced multi-functions

- A total of 20 memory channels are available
- Ideal compact size of 150(W)×50(H)×180(D) mm* to mount in various types of vehicles
*5²⁹/₃₂(W)×1³¹/₃₂(H)×7³/₃₂(D) in
- 36 W (pep) of powerful output
- Excellent durability to cope with even the toughest workplace
- Memory channel only operation possible via PC programming
- Hand microphone supplied

SPECIFICATIONS

GENERAL

- Frequency range : 118.000–136.975 MHz
- Channel spacing : 8.33/25 kHz auto selection (according to version) or 25 kHz only
- Mode : 6K00A3E (AM)
- No. of memory Ch. : 20
- Antenna connector : SO-239 (50 Ω)
- Power supply requirement: (negative ground) 13.75 V DC or 27.5 V DC automatic selection
- Current drain (at 13.75 V DC):
Transmitting 5.0 A max.
Receiving 4.0 A (at AF max.)
0.5 A (at stand-by)
- Operating temperature range:
IC-A110 -30°C to +60°C
; -22°F to +140°F
IC-A110EURO -20°C to +55°C
- Frequency stability :
IC-A110 ±5 ppm (-30°C to +60°C)
IC-A110EURO ±1 ppm (0°C to +40°C)
- Dimensions : 150(W)×50(H)×180(D) mm (projections not incl.)
5²⁹/₃₂(W)×1³¹/₃₂(H)×7³/₃₂(D) in
- Weight (approx.) : 1.5 kg; 3 lb 5 oz

Measurements made in accordance with RTCA D0-186a (Class C/E, Class 4/6) or EN 300 676. All stated specifications are and subject to change without notice or obligation.

*These specification items are not available for the IC-A110 due to approval test specifications.

Type approval for the IC-A110/EURO varies between countries. Ask your dealer for availability.

TRANSMITTER

- Output power : 36 W typ. pep (9 W typ. for CW)
- Modulation limiting : 70–100% (IC-A110)
- Modulation compression*: Linear 85%
Max. 95%
- AF harmonic distortion : Less than 10% (at 85% mod.)
- Hum and Noise ratio : More than 40 dB
- Spurious emissions :
IC-A110 Less than -16 dBm
IC-A110EURO Less than -46 dBm (Less than -36 dBm for harmonics in 30 MHz to 1 GHz range)
9 kHz to 1 GHz Less than -40 dBm (Less than -30 dBm for harmonics)
1–4 GHz Less than -40 dBm (Less than -30 dBm for harmonics)
- Adjacent Ch. power* : Less than 60 dB (25 kHz)
Less than 50 dB (8.33 kHz)
- Microphone connector : 8-pin modular (600 Ω)

RECEIVER

- Receiving system : Double conversion super-heterodyne
- Intermediate freq. : 1st 38.85 MHz
2nd 450 kHz
- Sensitivity (pd) :
IC-A110 Less than 1 μV (at 6 dB S/N)
IC-A110EURO Less than +5 dBμV (at 12 dB SINAD)
- Squelch sensitivity (pd; at threshold):
IC-A110 Less than 0.3 μV
IC-A110EURO Less than -6 dBμV
- Selectivity :
25 kHz Ch. spacing More than ±8 kHz (at -6dB)
Less than ±17 kHz (at -40dB)
Less than ±25 kHz (at -60dB)
8.33 kHz Ch. spacing More than ±2.778 kHz (at -6dB)
Less than ±7.37 kHz (at -60dB)
- Spurious response : More than 74 dBμ (IC-A110)
More than 70 dB (IC-A110EURO)
- Intermodulation rejection ratio*: More than 64 dB
- Blocking/desensitisation*: More than 70 dB
- Cross modulation rejection*: More than 70 dB
- Audio output power (at 13.75 V; 10% dist.; 60% mod.):
Internal speaker 1.5 W typical w/8 Ω load
External speaker More than 10.0 W w/8 Ω load
Headset (side tone) More than 0.1 W w/500 Ω load
- AF output impedance : EXT SP 8 Ω
Headset (side tone) 500 Ω

Supplied Accessories

- Hand microphone, HM-161
- DC power cable
- Mounting bracket kit
- Microphone hanger kit
- Fuses

OPTION



OPC-871 HEADSET ADAPTER
For connection with standard airband headset.



HM-161 HAND MICROPHONE
Same as supplied.

Applicable U.S. Military Specifications

Icom makes rugged products that have been tested to and passed the following MIL-STD requirements and strict environmental standards.

Standard	MIL 810 C		MIL 810 D		MIL 810 E	
	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I
Solar Radiation	505.1	I	505.2	I	505.3	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III
Salt Fog	509.1	I	509.2	I	509.3	I
Dust	510.1	I	510.2	I	510.3	I
Vibration	514.2	VIII, X	514.3	I	514.4	I
Shock	516.2	I, II, IV	516.3	I, IV	516.4	I, IV

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (01227) 741741
Fax : +44 (01227) 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0900
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0211) 346047
Fax : +49 (0211) 333639
E-mail : info@icom-europe.com
URL : <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejone des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
Road, Haidian District, Beijing, 100039, China
Phone : +86 (010) 5889 5391/5392/5393
Fax : +86 (010) 5889 5395
E-mail : bjicom@bjicom.com
URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
08190, Sant Cugat del Valles, Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska

Sopot, 3 maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolska.com.pl
URL : <http://www.icompolska.com.pl>